SALES FACT SHEET

RAPM- JAZ SERIES

Efficiencies up to 16.00 SEER/13.55 EER
Nominal Sizes 1.5 to 5 Tons
[5.28 kW] to [17.6 kW]
Cooling Capacities
18.8 to 62.5 kBTU
[5.50 kW] to [18.32 kW]

Rheem *Classic® Series* Air Conditioners



Features

- Attractive, louvered wrap-around jacket protects the coil from yard hazards and weather extremes. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all-weather protection.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction.
- Combination Grille/Motor Mount secures the motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- All controls are accessible by removing one service panel. Removable top grille provides access to the condenser fan motor and condenser coil.
- Single speed 8-pole fan motor designed for low speed, quiet, energy-saving operation.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.
Compressor . . . . . .Ten (10) Years
Conditional Parts (Registration Required) . . . . . .Ten (10) Years

MODEL	Nominal Cooling Capacity (BTU/HR)	VOLTAGE	PHASE	HEIGHT	WIDTH	LENGTH	Shipping Weight	Service Valve - Liquid	Service Valve - Suction	PRICE
018JAZ	18,000	208/230	1	19"	27 - 5/8"	40 - 1/2"	160.5	3/8"	3/4"	
024JAZ	24,000	208/230	1	29"	31 - 1/2"	44 - 3/8"	214.5	3/8"	3/4"	
030JAZ	30,000	208/230	1	29"	31 - 1/2"	44 - 3/8"	214	3/8"	3/4"	
036JAZ	36,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	227	3/8"	7/8"	
042JAZ	42,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	256	3/8"	7/8"	
048JAZ	48,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	298	3/8"	7/8"	
056JAZ	56,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	306.5	3/8"	7/8"	
060JAZ	60,000	208/230	1	33"	31 - 1/2"	44 - 3/8"	306.5	3/8"	7/8"	

ISO 9001:2008
Certificate Number: 30164

ENERGY STAR

ENERGUIDE
Seasonal Energy Efficiency Ratio (SEER)
13.0 — Uses least energy → 21.0

AHRI CERTIFIED
www.ahridirectory.org
Unitary Small AC
AHRI Standard 210/240

c UL us LISTED

"Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR criteria. Ask your Contractor for details or visit www.energystar.gov."

Rheem Heating, Cooling and Water Heating
P.O. Box 17010, Fort Smith, AR 72917

FORM NO. A11-217-SFS
PRINTED IN U.S.A. QG 10-12

SALES FACT SHEET

ACCESSORIES		
Description	Part No.	Price
Low Ambient Control (RXAD-A08)	RXAD-A08	
Compressor Time Delay Control	42-22655-02	
Crankcase Heater for 1.5 - 3 ton Models	44-17402-44	
Crankcase Heater for 3.5 - 5 ton Models	44-101884-01	
Sound Enclosure for 1.5 - 3 ton Models	68-23427-26	
Sound Enclosure for 3.5 - 5 ton Models	68-23427-25	

Total Price $